



## Introducing CCH® Phosphate Pro!

SKU 30499

Buy a Full Pallet of any  
CCH® Pro Line PMP and  
get **3 FREE** CCH® Feeder  
Dosing Pumps

CCH® Phosphate Pro is a NSF 50 certified pool maintenance product! With a more concentrated formula, available in 5 gallon containers and dosed with an automated pump, the CCH® Phosphate Pro makes commercial pool care and maintenance easier!



CCH® Phosphate Pro is a 3-in-1 concentrated product that provides remarkable pool water using half the dosing when compared to competitive products. When used as a weekly maintenance product, this unique product clarifies the water and prevents waterline build-up. In addition, it removes phosphates, helping to minimize algae blooms.

- 3-in-1 maintenance product that helps control phosphate levels
- Can help avoid cloudiness in water
- Add 2 ounces of this product into the skimmer weekly for every 10,000 gallons of pool water

The Model Aquatic Health Code (MAHC) is moving towards requiring all pool chemicals to be NSF certified. CCH® strives to meet evolving community, state, and national water standards with innovative solutions!



In an effort to ensure ease of use, the CCH® Phosphate Pro can be dosed multiple ways!



### Best Option

SKU 74457

#### Using the CCH® Feeder Dosing Pump!

Featuring a 10g rotomolded tank with integrated Stenner pump – just add two 5-gallon containers of product and set to auto dosing specific to chemistry and pool size.

Buy a Full Pallet of any CCH® Pro Line PMP and get **3 FREE** CCH® Feeder Dosing Pumps



### Better Option

SKU 74445

#### Using the Stenner pump only!

Pump can be wall mounted with tubing connected to product container and set to auto dosing to specific chemistry and pool size.



### Good Option

#### Using a hand pump!

Hand pump can be inserted into the top of the product container and dosed to specific chemistry and pool size.

CCH® Phosphate Pro Dosing Chart

Gallons of Pool Water	Pump Setting	Hand Pump Dosing (oz)
25,000	2.5	5
50,000	5	10
100,000	10	20
150,000	15	30
200,000	20	40
250,000	25	50
300,000	30	60
500,000	50	100
750,000	75	150
1,000,000	100	200

Pump Operating Parameters

Default Output*	Up to 0.45 gal/day	Up to 1.7L/day
Max Pressure	80 psi	5.5 bar
Max Temperature	104 °F	40 °C
Motor Voltage (Amp Draw)	120V 60Hz	

\*Output of up to 9.5 gallons (36L) per day is available with larger peristaltic tubing

For more information visit [www.cchpoolcare.com](http://www.cchpoolcare.com) or call us at 1-800-478-5727